Lutz+Partner Multimedia
Lutz-Electronics

YAESU
Choice of the World's top DX'ers

FT-991A

HF/VHF/UHF All-Mode "Field Gear" Transceiver

Radio Features:

- Dynamic Real-Time Spectrum Scope *NEW!
- Multi-Color Waterfall Display *NEW!
- 160 Meters through 70 Centimeters - SSB/CW/FM/C4FM Digital/AM
- 100 Watts (2 Meter / 70 Centimeter: 50 Watts) of Solid Output Power Performance
- 3.5 inch TFT Full-Color Touch Panel Operation for Superior Operability and Visibility
- Advanced Functions such as High-Quality Audio Transmission, AMS, and Group Monitor utilizing C4FM Digital
- Triple Conversion Circuit (SSB/CW/AM) /Double Conversion (FM/C4FM) Configuration, 1st IF is set at 69.450 MHz
- Roofing Filters 3 kHz and 15 kHz as standard equipment
- IF WIDTH and IF SHIFT providing great QRM Rejection
- CONTOUR, DNR, IF Notch and APF (Audio Peak Filter, CW only)
- 160 - 6 Meters High Speed Automatic Antenna Tuner included
- High Accuracy TCXO □0.5 ppm
- Built-in Electronic Keyer
- CW Message Memory with Beacon Mode
- CW Pitch□/□Sidetone Control
- Automatic Repeater Shift
- USB Connector (CAT control, Audio interface, PTT/SHIFT control)
- Two Antenna Connectors (HF/50MHz, 144/430MHz)
- Optional FC-40 Automatic Antenna Tuner (for long wire antenna) is connectable
- Optional ATAS-120A Active Tuning Antenna is connectable

* Data FR mode (high speed data communication mode) is not supported, and transmission and reception of image data by C4FM digital is not possible

Supplied Accessories:

Hand Microphone (MH-31A8J)
DC Power Cord
Spare Fuse (25A)
Operating Manual
Warranty Card

Specifications:

Frequency Ranges: RX 30 kHz - 56 MHz, 118 MHz - 164 MHz, 420 MHz - 470 MHz (specified performance, amateur bands only)
TX 1.8 MHz - 54 MHz, 144 MHz - 146 MHz, 430 MHz - 440 MHz (amateur bands only)
Circuit Type: Triple-Conversion Superheterodyne: SSB/CW/AM
Double-Conversion Superheterodyne: FM/C4FM
Modulation Type: A1A(CW), A3E(AM), J3E(LSB, USB), F7W(C4FM), F3E(FM),
F1D(PACKET), F2D(PACKET)
Power Output: SSB/CW/FM AM Carrier
160- 6 Meters: 100 W 25 W
2 Meters/70 Centimeters: 50 W 12.5 W
Case Size(W x H x D): 229 mm x 80 mm x 253 mm (w/o knob and connector)
Weight: 4.3 kg
Qty in Master Carton: 4
Warranty: 3 Years
FACTORY MUTUAL APPROVAL
FACTORY MUTUAL APPROVAL



Der neue FT-991 A wird bei uns ab Oktober 2016 ab Lager verfügbar sein.

YAESU ist bemüht für die Besitzer des aktuellen Modells FT-991 ein entsprechendes Hardware-Upgrade-Package für die Erweiterung ihres TRX mit den zusätzlichen Features des neuen FT-991**A (im Wesentlichen das Echtzeit-Spektrum Scope mit Wasserfallanzeige)** zu attraktiven Konditionen zu erarbeiten. Detaillierte Informationen werden auf www.lutz-electronics.ch folgen.